



HYDRA-FLEX
HOSE AND FITTINGS
SOLUTIONS CENTER

XTRALOCK TYPE

MF2000®

DIAMONDSPIR HOSE RANGE


M68690

90° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3

BRIDA 90° ISO/SAE CODIGO 62 - SAE J516 / ISO 12151-3

90° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 90° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm			
	DN	inch	Size		B	A	D	E
M68690-12-12	19	3/4"	-12	3/4"	16,0	75,0	41,4	59,0
M68690-16-16	25	1"	-16	1"	20,0	89,0	47,7	80,0
M68690-20-20	31	1.1/4"	-20	1.1/4"	24,0	110,0	54,2	93,0
M68690-24-24	38	1.1/2"	-24	1.1/2"	38,5	125,0	63,7	110,0
M68690-32-32	51	2"	-32	2"	42,0	148,0	79,6	136,0


M68640

45° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3

BRIDA 45° ISO/SAE CODIGO 62 - SAE J516 / ISO 12151-3

45° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 45° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm			
	DN	inch	Size		B	A	D	E
M68640-16-16	25	1"	-16	1"	20,0	98,5	47,7	38,0
M68640-20-20	31	1.1/4"	-20	1.1/4"	24,0	121,5	54,2	43,5
M68640-24-24	38	1.1/2"	-24	1.1/2"	38,5	136,0	63,7	50,0
M68640-32-32	51	2"	-32	2"	42,0	160,0	79,6	61,0