



CRIMPING MACHINES

MODEL	MACHINE TYPE	APPLICATION SECTOR	INDICATIVE CAPACITY	CRIMP FORCE (TONS)	VOLTAGE	WEIGHT (KG. LBS)
MHP80 	hand pump, portable	on-site repair	2wb: 1" max. 4ws: 1/2" max.	80	-	28 kg (60 lbs)
MVB140 	benchtop, cage dies	on site repair, after market service	2wb: 1-1/4" max. 4ws: 1-1/4" max.	140	110V, 1ph, 60Hz	80kg (176 lbs)
MB137 PLUS 	benchtop	after market service	2wb: 1-1/4" max. 4ws: 1-1/4" max.	137	220V, 3ph, 60Hz 110V, 1ph, 60Hz	100 kg (220 lbs)
MB240 	benchtop	after market service	2wb: 2" max. 4ws: 2" max. 6ws: 1" max.	240	240V, 3ph, 60Hz	190 kg (418 lbs)
MB350 	benchtop	after market service	2wb: 3" max. Textile and suction hose: 4" max. 4ws: 2" max. 6ws: 2" max.	350	240V, 3ph, 60Hz	280 kg (617 lbs)
MV240 	for mobile van	on site repair mobile van	2wb: 2" max. 4ws: 2" max. 6ws: 1" max.	240	12dc or 24dc	125 kg (275 lbs)
MS140 	stand-type SCS control	assembling production unit	2wb: 1-1/4" max. 4ws: 1-1/4" max.	140	240V, 3ph, 60Hz	675 kg (1485 lbs)
MS320 	stand-type SCS control	assembling production unit	2wb: 3" max. 4ws: 2" max. 6ws: 2" max.	320	240V, 3ph, 60Hz	1330 kg (2900 lbs)
MS400 	stand-type SCS control	assembling production unit	2wb: 3" max. 4ws: 3" max. 6ws: 3" max.	400	240V, 3ph, 60Hz	2000 kg (4400 lbs)
MS500 	stand-type SCS control	assembling production unit	4" max. heavy duty hydraulic hoses 8" max. industrial hoses	450	240V, 3ph, 60Hz	3000 kg (6614 lbs)