




Clamps

Double Bolt Clamps

Features:

- inner surface has dual gripping ridges
- bolt lugs are reinforced to prevent bending out of alignment
- Torque values for clamps are based on dry bolts.
- The use of lubricant on bolts will adversely effect clamp performance. 
- measure hose OD accurately before ordering clamps
- Consult Dixon when using double bolt clamps on helical wire hose.



without saddles



with saddles

| Hose OD | | Plated Iron | | Opt Qty | Torque in ft. lbs. |
|----------|----------|-------------------------|--|---------|--------------------|
| from | to | Part # | | | |
| 1-8/64" | 1-12/64" | J48 | | 100 | 15 |
| 1-12/64" | 1-24/64" | J49 | | 50 | 21 |
| 1-28/64" | 1-34/64" | JX49 | | 25 | 21 |
| 1-40/64" | 1-52/64" | DL14 | | 25 | 40 |
| 1-48/64" | 2-3/64" | DL20 | | 25 | 27 |
| 2-7/64" | 2-19/64" | DL24¹ | | 25 | 27 |
| 2-20/64" | 2-40/64" | DL32¹ | | 25 | 40 |
| 2-32/64" | 2-48/64" | DL275 | | 25 | 40 |
| 2-48/64" | 3-4/64" | DL306 | | 20 | 60 |
| 3-4/64" | 3-24/64" | DL328 | | 20 | 60 |
| 3-16/64" | 3-32/64" | DL350 | | 20 | 60 |


| Hose OD | | Plated Iron | | Opt Qty | Torque in ft. lbs. |
|-----------|-----------|-------------|--|---------|--------------------|
| from | to | Part # | | | |
| 3-32/64" | 3-52/64" | 400 | | 25 | 40 |
| 3-50/64" | 4-4/64" | 431 | | 20 | 40 |
| 4-2/64" | 4-18/64" | 463 | | 20 | 40 |
| 4-16/64" | 4-60/64" | 525 | | 10 | 60 |
| 4-32/64" | 5-16/64" | 550 | | 10 | 60 |
| 5-8/64" | 5-44/64" | 600 | | 10 | 60 |
| 5-44/64" | 5-60/64" | 639 | | 10 | 60 |
| 5-60/64" | 6-32/64" | 675 | | 10 | 60 |
| 6-32/64" | 7-36/64" | 769 | | 10 | 60 |
| 7-44/64" | 8-12/64" | 818 | | 5 | 125 |
| 8-16/64" | 8-56/64" | 875 | | 5 | 125 |
| 8-60/64" | 9-56/64" | 988 | | 5 | 125 |
| 9-60/64" | 11-24/64" | 1125 | | 5 | 125 |
| 11-12/64" | 13" | 1275 | | 3 | 125 |
| 12-12/64" | 14" | 1360 | | 2 | 200 |
| 13-12/64" | 15" | 1450 | | 2 | 200 |
| 15-4/64" | 17-32/64" | 1700 | | 2 | 260 |

¹ investment cast carbon steel

K

Single Bolt Clamps

Features:

- measure hose OD accurately before ordering clamps
- Torque values for clamps are based on dry bolts.
- The use of lubricant on bolts will adversely effect clamp performance. 



| Hose OD | | Plated Iron | | Torque in ft. lbs. |
|----------|----------|-------------|--|--------------------|
| from | to | Part # | | |
| 56/64" | 1" | 2 | | 6 |
| 62/64" | 1-8/64" | 3 | | 6 |
| 1-4/64" | 1-12/64" | 4 | | 6 |
| 1-10/64" | 1-16/64" | 5 | | 6 |
| 1-16/64" | 1-24/64" | 6 | | 6 |
| 1-22/64" | 1-28/64" | 7 | | 6 |
| 1-28/64" | 1-36/64" | 8 | | 6 |
| 1-34/64" | 1-44/64" | 9 | | 6 |
| 1-42/64" | 1-48/64" | 10 | | 6 |
| 1-48/64" | 1-56/64" | 11 | | 6 |
| 1-56/64" | 2-2/64" | 12 | | 6 |
| 2" | 2-8/64" | 13 | | 12 |
| 2-8/64" | 2-18/64" | 14 | | 12 |
| 2-16/64" | 2-26/64" | 15 | | 12 |

| Hose OD | | Plated Iron | | Torque in ft. lbs. |
|----------|----------|-------------|--|--------------------|
| from | to | Part # | | |
| 2-24/64" | 2-32/64" | 16 | | 12 |
| 2-32/64" | 2-40/64" | 17 | | 12 |
| 2-40/64" | 2-56/64" | 18 | | 12 |
| 2-56/64" | 3-4/64" | 19 | | 12 |
| 3-4/64" | 3-16/64" | 20 | | 12 |
| 3-16/64" | 3-28/64" | 21 | | 12 |
| 3-28/64" | 3-40/64" | 22 | | 21 |
| 3-40/64" | 3-52/64" | 23 | | 21 |
| 3-52/64" | 4-8/64" | 24 | | 21 |
| 4-8/64" | 4-20/64" | 25 | | 21 |
| 4-16/64" | 4-32/64" | 26 | | 21 |
| 4-28/64" | 4-40/64" | 27 | | 21 |
| 4-40/64" | 4-56/64" | X27 | | 21 |
| 4-56/64" | 5-16/64" | 28 | | 21 |