



FUEL INJECTION

FUEL INJECTION HOSE

FUEL INJECTION SAE 30R9



Product Specifications

Application: Designed specifically for auto and truck fuel injection systems. Goodyear Engineered Products SAE 30R9 is CARB approved (C-U-06-011) with a maximum fuel permeation of 15g/m²/day at 40°C.

Specific Fuel: Gasoline, ethanol extended gasoline, oxidized sour gas, diesel fuel, biodiesel, lubrication oil

CONSTRUCTION

TUBE: Black Fluoroelastomer/Nitrile (Effective 2010)

COVER: Black Hypalon* (CSM)

REINFORCEMENT: Aramid Spiral

TEMPERATURE: -34°C to 135°C (-29°F to 275°F) Intermittent use at 150°C (302°F)

BRANDING LAYLINE: Goodyear ID" (mm) Fuel Injection Hose SAE J30R9 Country of Origin

WARNING: DO NOT SUBMERSE IN GASOLINE

SAE 30R9 FUEL HOSE

PART NUM	ID		Lengths (ft)	Working Pressure				WEIGHT (lbs./ft.)
	Id(in)	OD(in)		Working Pressure(PSI)	Burst Pressure(PSI)	MIN Bend Radius(in)	Vacuum HG(in)	
65148	1/4	.50	1.5	Max 100	900	0.75	24	0.10
65148	1/4	.50	25	Max 100	900	0.75	24	0.10
65301	1/4	.50	250	Max 100	900	0.75	24	0.10
65149	5/16	.56	1.5	Max 100	900	0.84	24	0.12
65152	5/16	.56	25	Max 100	900	0.84	24	0.12
65302	5/16	.56	250	Max 100	900	0.84	24	0.12
65150	3/8	.63	1.5	Max 100	900	0.94	24	0.14
65153	3/8	.63	25	Max 100	900	0.94	24	0.14
65303	3/8	.63	250	Max 100	900	0.94	24	0.14
65164	1/2	.80	50	Max 100	900	2.00	24	0.16