

















102D BACK CONNECTED 1-1/2" DIAL WITH 1/8" NPT CONNECTION

- An inexpensive utility gauge for the broad commercial and industrial markets.
- · Suitable for air, water, oil, gas or any other media not corrosive to brass.
- Other connection locations, mounting styles and accessories available.
- · Ready for immediate shipment upon request.

SPECIFICATIONS:

DIAL SIZE: 1 ½"


CONNECTION SIZE: 1/8"NPT

- . Black Steel Case, Chrome Bezel
- · Phosphor Bronze Bourdon Tube
- Brass Socket
- Polycarbonate Lens
- 3-2-3 % Accuracy
- Dry Non-Fillable
- Ambient Temperature: -50 to 160'F
- Dual scale: PSI & Bar (x100=kpa) standard Single scale: PSI only available
 - Other:

by special request



PART#	RANGE	CODE	Major Inc.	Minor Inc.
102D-158A	30/0"VAC	Α	5" hg	.5" hg
102D-158B	0/15	В	2 PSI	.2 PSI
102D-158C	0/30	С	5 PSI	.5 PSI
102D-158D	0/60	D	10 PSI	1 PSI
102D-158E	0/100	E	20 PSI	2 PSI
102D-158F	0/160	F	20 PSI	2 PSI
102D-158G	0/200	G	40 PSI	5 PSI
102D-158H	0/300	Н	50 PSI	5 PSI
102D-158I	0/400		50 PSI	5 PSI
102D-158K	0/600	K	100 PSI	10 PSI
102D-158M	0/1000	M	200 PSI	20 PSI
102D-158N	0/1500	N	200 PSI	20 PSI
102D-158O	0/2000	0	400 PSI	50 PSI
102D-158P	0/3000	Р	500 PSI	50 PSI
102D-158R	0/5000	R	1000 PSI	100 PSI
102D-158S	0/6000	S	1000 PSI	100 PSI
102D-158U	0/10,000	U	2000 PSI	200 PSI



		Α	В	С	D	E
1 1/2"	In.	1.64"	.93"	.63"	1.56"	1/8"
Dial	MM	42	24	16	39	MNPT



















102D BACK CONNECTED 2" DIAL WITH 1/8" NPT CONNECTION

- An inexpensive utility gauge for the broad commercial and industrial markets.
- Suitable for air, water, oil, gas or any other media not corrosive to brass.
- Other connection locations, mounting styles and accessories available.
- Ready for immediate shipment upon request.

SPECIFICATIONS:


DIAL SIZE: 2"

CONNECTION SIZE: 1/8"NPT

- Black Steel Case, Chrome Bezel
- **Phosphor Bronze Bourdon Tube**
- **Brass Socket**
- Polycarbonate Lens
- 3-2-3 % Accuracy
- Dry Non-Fillable
- Ambient Temperature: -50 to 160'F
- Dual scale: PSI & Bar (x100=kpa) standard available Single scale: PSI only Other: by special request



PART#	RANGE	CODE	Major Inc.	Minor Inc.
102D-208A	30/0"VAC	A	5" hg	.5" hg
102D-208B	0/15	В	2 PSI	.2 PSI
102D-208C	0/30	С	5 PSI	.5 PSI
102D-208D	0/60	D	10 PSI	1 PSI
102D-208E	0/100	E	20 PSI	2 PSI
102D-208F	0/160	F	20 PSI	2 PSI
102D-208G	0/200	G	40 PSI	5 PSI
102D-208H	0/300	Н	50 PSI	5 PSI
102D-208I	0/400		50 PSI	5 PSI
102D-208K	0/600	K	100 PSI	10 PSI
102D-208M	0/1000	M	200 PSI	20 PSI
102D-208N	0/1500	N	200 PSI	20 PSI
102D-208O	0/2000	0	400 PSI	50 PSI
102D-208P	0/3000	Р	500 PSI	50 PSI
102D-208R	0/5000	R	1000 PSI	100 PSI
102D-208S	0/6000	S	1000 PSI	100 PSI
102D-208U	0/10,000	U	2000 PSI	200 PSI
102D-208B	0/15	В	2 PSI	.2 PSI
102D-208C	0/30	С	5 PSI	.5 PSI
102D-208D	0/60	D	10 PSI	1 PSI
102D-208E	0/100	E	20 PSI	2 PSI
102D-208F	0/160	F	20 PSI	2 PSI
102D-208G	0/200	G	40 PSI	5 PSI



		Α	В	C	D	E	
2"	ln.	2.07"	1.03"	.83"	1.86"	1/8	Ī
Dial	MM	53	26	21	47	MNPT	



















102D BACK CONNECTED 2" DIAL WITH 1/4" NPT CONNECTION

- An inexpensive utility gauge for the broad commercial and industrial markets.
- Suitable for air, water, oil, gas or any other media not corrosive to brass.
- · Other connection locations, mounting styles and accessories available.
- · Ready for immediate shipment upon request.

SPECIFICATIONS:


DIAL SIZE: 2"

CONNECTION SIZE: 1/4"NPT

- Black Steel Case, Chrome Bezel
- Phosphor Bronze Bourdon Tube
- Brass Socket
- Polycarbonate Lens
- 3-2-3 % Accuracy
- Dry Non-Fillable
- Ambient Temperature: -50 to 160'F
- Dual scale: PSI & Bar (x100=kpa) standard
 Single scale: PSI only available
 Other: by special request



PART#	RANGE	CODE	Major Inc.	Minor Inc.
102D-204A	30/0"VAC	Α	5" hg	.5" hg
102D-204B	0/15	В	2 PSI	.2 PSI
102D-204C	0/30	С	5 PSI	.5 PSI
102D-204D	0/60	D	10 PSI	1 PSI
102D-204E	0/100	E	20 PSI	2 PSI
102D-204F	0/160	F	20 PSI	2 PSI
102D-204G	0/200	G	40 PSI	5 PSI
102D-204H	0/300	Н	50 PSI	5 PSI
102D-204I	0/400		50 PSI	5 PSI
102D-204K	0/600	K	100 PSI	10 PSI
102D-204M	0/1000	М	200 PSI	20 PSI
102D-204N	0/1500	N	200 PSI	20 PSI
102D-204O	0/2000	0	400 PSI	50 PSI
102D-204P	0/3000	Р	500 PSI	50 PSI
102D-204R	0/5000	R	1000 PSI	100 PSI
102D-204S	0/6000	S	1000 PSI	100 PSI
102D-204U	0/10,000	U	2000 PSI	200 PSI



		Α	В	С	D	E
2"	In.	2.07"	1.03"	.83"	1.86"	1/4
Dial	MM	53	26	21	47	MNPT



















102D BACK CONNECTED 2-1/2" DIAL WITH 1/4" NPT CONNECTION


- An inexpensive utility gauge for the broad commercial and industrial markets.
- · Suitable for air, water, oil, gas or any other media not corrosive to brass.
- · Other connection locations, mounting styles and accessories available.
- · Ready for immediate shipment upon request.

SPECIFICATIONS:

- DIAL SIZE: 2 ½"
- AVAILABLE CONNECTION SIZES: 1/4"NPT
- Black Steel Case, Chrome Bezel
- Phosphor Bronze Bourdon Tube
- Brass Socket
- Polycarbonate Lens
- 3-2-3 % Accuracy
- Dry Non-Fillable
- Ambient Temperature: -50 to 160'F
- Dual scale: PSI & Bar (x100=kpa) standard Single scale: PSI only available
 - Other: by special request



PART#	PART # RANGE C		Major Inc.	Minor Inc.
102D-254A	30/0"VA	Α	5" hg	.5" hg
102D-254B	0/15	В	2 PSI	.2 PSI
102D-254C	0/30	С	5 PSI	.5 PSI
102D-254D	0/60	D	10 PSI	1 PSI
102D-254E	0/100	E	20 PSI	2 PSI
102D-254F	0/160	F	20 PSI	2 PSI
102D-254G	0/200	G	40 PSI	5 PSI
102D-254H	0/300	Н	50 PSI	5 PSI
102D-254I	0/400		50 PSI	5 PSI
102D-254K	0/600	K	100 PSI	10 PSI
102D-254M	0/1000	M	200 PSI	20 PSI
102D-254N	0/1500	N	200 PSI	20 PSI
102D-254O	0/2000	0	400 PSI	50 PSI
102D-254P	0/3000	Р	500 PSI	50 PSI
102D-254R	0/5000	R	1000 PSI	100 PSI
102D-254S	0/6000	S	1000 PSI	100 PSI
102D-254U	0/10,00	U	2000 PSI	200 PSI
102D-254B	0/15	В	2 PSI	.2 PSI
102D-254C	0/30	С	5 PSI	.5 PSI
102D-254D	0/60	D	10 PSI	1 PSI
102D-254E	0/100	E	20 PSI	2 PSI
102D-254F	0/160	F	20 PSI	2 PSI
102D-254G	0/200	G	40 PSI	5 PSI



		Α	В	C	D	E
2 1/2"	In.	2.50"	1.17"	.86"	2.03"	1/4
Dial	MM	63	30	22	52	MNPT